



Looking for a flexible solution?



You prefer automatic meter reading systems to control energy, use it efficiently and save up. What is your preference to use automatic meter reading systems in the most efficient and economical way?

VHS Electronics offers the most advanced OSOS modem, which is designed in a redundant communication structure, capable of local backup of your data for years, which will minimize operating costs, enable you to access the data you need in all circumstances.

Expectation from a correctly constructed and well-functioning OSOS system; stable and continuous data transfer with low operating costs. VHS COMBI is designed to use both GPRS and Ethernet infrastructure in a single device.



OSOS.net It provides communication over Ethernet.





OSOS.3 It provides communication over GSM-GPRS network.





Technical Features	0\$0\$.3	OSOS.net	OSOS.kombi
Arm Cortex 32 Bit Microprocessor	 ✓ 	 Image: A second s	\checkmark
Up to 4 GB of Internal Memory			~
Status and Alarm LEDs	4 piece	6 piece	6 piece
Ethernet Port	Х	~	~
GSM/GPRS	 ✓ 	Х	\checkmark
RS232, RS485, IEC62056 Optical Ports			~
Internal Real Time Clock (RTC)	 Image: A second s	 Image: A set of the set of the	\checkmark
Optional Digital Input	8 piece*	8 piece	8 piece
Optional Analog input	3 piece*	4 piece	4 piece
Digital Outputs	4 piece**	4 piece**	4 piece**
Aesthetic design and durable outer body	 Image: A second s	~	\checkmark
Operating temperature of large range	~	~	~
Low Power (<5Watt)	 Image: A second s	~	\checkmark
Advanced Alarm Features	\checkmark	\checkmark	~
Functional Features	0\$0\$.3	OSOS.net	OSOS.kombi
Network Communication with Backup	×	X	\checkmark
Auto Communication	×	×	~
Channel Swicthing			
Infinite virtual memory	X	 Image: A second s	\checkmark
Advanced I/O	X	X	X
New Generation ARM Cortex	 ✓ 	 Image: A second s	\checkmark
Processor & Low Power & High Performans			
Autonomous mission applications, independent	~	~	~
of the central system			
Specific log storage in memory	 Image: A second s	 Image: A second s	\checkmark
Flexible connection port	X	~	~
Datalogger Capability	X	 Image: A second s	\checkmark
Packet identification in Modem	\checkmark	~	\checkmark
Brand independent. Field studies were carried out with	 Image: A set of the set of the	~	~
different meter brands that are used extensively in			
the sector.			
Communication with different GSM Operators	~	×	~
in same network			
Static/Dynamic IP	Image: A state of the state	 Image: A set of the set of the	 Image: A second s
Different Control/Command facility with same device	~	~	~
Remote power OFF/ON functions	 Image: A set of the set of the	\checkmark	 Image: A second s
Read/Write Features such that	~	✓	~
Energy Analyzer, Reaktif Power Control Relay			
High Level data security and authenication	~	 Image: A second s	 Image: A second s
(Data Transfer by Cryptographic)			
Instant transmission of alarm information to the center	~	~	\checkmark
Remote parameter setting and	 ✓ 	~	~
firmware update			
Terminal cover opened sensor	~	~	\checkmark
Instant transmission of Power OFF	 Image: A second s	~	~

akses.com.tr | info@akses.com.tr

0 İvedik OSB 2224. Cadde E Blok,

No:1, E213 Yenimahalle/Ankara/TURKEY

🕲 +90 312 502 4055

▣ +90 312 230 7261

🖂 info@akses.com.tr

www. akses.com.tr



Яł,

alarm to the center





